



°C

+85

max

| Product designation Product type designa | tion | | | Selector switch actuators lever - 2 position LPCS12 |
|---|-----------------------|-----|--------|--|
| General characteristic | | | | |
| Colour | | | | Black |
| Type of positions | | | | 0 - 1 |
| Material | | | | Polyamide |
| IEC degree of protection | | | | IP66, IP67 and IP69K |
| Mechanical features | | | | |
| Mechanical life | | | cycles | 1000000 |
| Mounting adapter | | | | LPXAU120 |
| Weight | | g | 37 | |
| UL technical data | | | | |
| UL degree of protection | | | | Type1, 2, 3R, 4, 4X, 12, 12K |
| Ambient conditions | | | | |
| Temperature | | | | |
| | Operating temperature | | | |
| | | min | - | -25 |
| | | max | °C | +70 |
| | Storage temperature | | | |
| | | min | °C | -40 |

Dimensions



Certifications and compliance

| Complian | ce | |
|-------------|---|-------|
| | CSA C22.2 n° 14 | |
| | IEC/EN/BS 60947-1 | |
| | IEC/EN/BS 60947-5-1 | |
| | UL508 | |
| Certificate | 95 | |
| | CCC | |
| | cULus | |
| ETIM clas | sification | |
| LPCS120 | The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding | 1 / 2 |

LPCS120 WAHLSCHALTER MIT DREHKNOPF Ø22MM PLATINUM SERIE, KUNSTSTOFF MIT VERCHROMUNG, 2 POSITIONEN, 0 - 1



ETIM 8.0

EC000222 -Front element for selector switch