LPMLP4

LED BLOCKLEUCHTANZEIGE, DAUERLICHT, Ø22MM PLATINUM SERIE, KUNSTSTOFF MIT VERCHROMUNG, ROT, 380,,,415VAC

Product designation			LED integrated monoblock pilot lights steady light
Product type designation			LPML
General characteristics			
Colour			Red
Type of positions			Monoblock pilot light
Material			Polyamide
IEC degree of protection			IP66, IP67 and IP69K on front; IP20 on rear
Electrical characteristics			
Rated frequency		Hz	50-60
Supply voltage (AC)		V	380…415 (-15% … +10% Ue)
Operations			
Electrical life		hours	>30000
Mechanical features			
Tightening torque for terminals max		Nm	0.8
Conductor section			
	AWG/kcmil conductor section		
	min		18
	max		16
	IEC		
	min	mm²	0.5
	max	mm²	2.5
Weight		g	24
UL technical data			
UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K on front
Ambient conditions			
Temperature			
	Operating temperature		
	min	°C	-25
	max	°C	+70
Dimensions			

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

LPMLP4

LED BLOCKLEUCHTANZEIGE, DAUERLICHT, Ø22MM PLATINUM SERIE, KUNSTSTOFF MIT VERCHROMUNG, ROT, 380,,,415VAC



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-5-1
UL508

Certificates

cULus
EAC

ETIM classification

ETIM 8.0	EC000272 - Indicator light complete

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding