Lovato electric
ENERGY AND AUTOMATION

11BGX1022

HILFSKONTAKTBLOCK FÜR BGX, 2S+2Ö

Product designation			Auxiliary contact
Product type designation			11BGX10
Contact characteristics			
Number of poles		Nr.	4
Rated insulation voltage Ui IEC/EN		V	690
Rated impulse withstand voltage Uimp		kV	6
IEC Conventional free air thermal current Ith		A	10
Tightening torque for terminals			
	min	Nm	0.8
	max	Nm	1
	min	Ibin	9
	max	Ibin	9
Tightening torque for coil terminal			
	min	Ibin	9
	max	Ibin	9
Max number of wires simultaneously connectable		Nr.	2
Conductor section			
AWG/Kcmil			
	max		12
Flexible w/o lug conductor section			
	min	mm²	0.75
	max	mm²	2.5
Flexible c/w lug conductor section			
	min	mm²	0.75
	max	mm²	2.5
Flexible with insulated spade lug conductor section			
	min	mm²	0.75
	max	mm²	2.5
Mechanical features			
Operating position			
	normal		On vertical plane
	allowable		Any
Fixing			Front centre mounting
Weight		g	28
Terminals screw			Screw
Auxiliary contact characteristics			
Type of contact			2NO + 2NC
Thermal current Ith		A	10
IEC/EN 60947-5-1 designation			A600 - Q600
Operating current AC15			
	230V	A	3
	400V	A	1.9
	500V	A	1.4
Operating current DC13			

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

	24V	A	3
	48V	A	1.5
	60V	A	1.2
	110V	A	0.6
	125V	A	0.55
	220V	A	0.27
	600V	A	0.1

Electrical characteristics

Conductivity			5V 10 mA
UL/CSA and IEC/EN 60947-5-1 designation			A600 Q600
Operating current AC15			
	120V	A	6
	240V	A	3
	480V	A	1.5
	600V	A	1.2
Operating current DC13			
	12V	A	10
	250V	A	0.27
	440V	A	0.15
	500V	A	0.13

UL technical data

Rated operational voltage AC (UL)		V	600

Ambient conditions

Temperature			
Operating temperature			
	min	°C	-50
	max	°C	+70
Storage temperature			
	min	°C	-60
	max	°C	+80
Max altitude		m	3000

Dimensions



Wiring diagrams

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

11BGX1022

HILFSKONTAKTBLOCK FÜR BGX, 2S+2Ö



Certifications and compliance

Compliance

CSA C22.2 n° 60947-1
CSA C22.2 n° 60947-5-1
IEC/EN 60947-1
IEC/EN 60947-5-1
UL 60947-1
UL 60947-5-1

Certificates

CCC
cULus
EAC

ETIM classification

ETIM 8.0	EC000041 - Auxiliary contact block

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding